Digital Tachometer with combined laser and mechanical contact

15117465

Combined contact and non-contact digital tachometer which measures rotation rate and surface speeds.

The tachometer includes, reflective tape, cone tip, flat tip, and wheel attachments for measuring surface speeds. 3 pcs. of 1,5V AA batteries included. Comes with a foam-fitted, hard-plastic storage box.

- Measures rotation in RPM
- Measures surface speed in m / min.
- Memory automatically remembers 3 values - last, highest and lowest value.

Measuring range:

- 2,5 ~ 99999 RPM (r/min) non-contact speed
- 0,5 ~ 19999 RPM (r/min) contact speed
- 0,05 ~ 1999,9 RPM (r/min) contact surface speed

Resolution:

Non-contact speed:
0,1 RPM (r/min) (2,5 ~ 999,9 RPM), 1 RPM (r/min) (over 1000 RPM)

Contact speed:
0,1 RPM (r/min) (0,5 ~ 999,9 RPM), 1 RPM (r/min) (over 1000

Product details	
Item no.	15117465
EAN	
Customs tariff	9029100090
Sales Quantity	1

Product specifications	
Barcode	5708004074878
Display type	5-digit LCD display with large screen. Character height 18 mm.
Battery	3 x 1,5V AA
Product size	155 x 70 x 35 mm
Accuracy	±0,05%
Dimensions	193 x 60 x 29 mm
Contact measurement	2,5-99999RPM
Data logging	3 values
Gross weight	0.590 kg
Net weight	0.180 kg