



Infrared thermometer with circular laser (-50°C-550°C)

15120170

Infrared thermometer with the latest technology and a beautiful color display. Adjustable emission factor from 0.1 to 1.00 makes the instrument unique for measurement on subjects with different surfaces. HI/LOW Alarm Function makes it easy and quick to make spot measurements. The circular laser allows you to clearly see the measured area.

1x9V battery included.

Important information:

- If the temperature in the working environment suddenly changes, the instrument must be placed in the environment for min. 30 minutes before measurement can be resumed. The measurement can only be resumed when the temperature inside the meter matches the temperature outside.
- The electromagnetic field from electronic welding and inductive heating must be minimized.
- Do not place the instrument near or directly on a hot object.
- The meter must be kept clean so that dust does not enter the lens
- Remember to turn the connector on the K-type correctly (plus to plus and minus to minus)

Product details

Item no.	15120170
EAN	5708004054702
Customs tariff	9025808090
Sales Quantity	1

Product specifications

Barcode	5708004054702
Working temperature	0~40°C
Auto power off	After 15 seconds
Backlight	Yes
Battery	6F22 1x9V (incl.)
Dimensions	163 x 97 x 33 mm
Color display	Yes
HOLD	Yes
Category	EN61326, EN60825
K-type	No
Laser target point	Cirkel (<1mW 630nm ~ 650nm)
Measuring range	-30°C-500°C
Measuring device	Celsius/Fahrenheit
Ambient temperature	Yes
Response time	<0.5 S
Spectral response	8 ~ 14um
Radiation ability	0,10 ~1,00
Temperature bridge alarm	Yes, (Red/Green LED)
UV light	No
Show low battery	Yes
Gross weight	0.320 kg
Net weight	0.200 kg