

## Surface Roughness Tester 4 standards, Ra, Rz, Rq, Rt

## 15215015

This simple roughnes tester has been developed for use in the workplace, for quick and easy control of milled, turned, sanded surfaces, on steel and other similar solid materials.

The roughness tester has a large display  $45 \times 19 \text{ mm}$  (front) and  $25 \times 6 \text{ mm}$  (top). It has a built-in rechargeable Lithium-ion battery (without memory effect), with a working time of approx. 20 hours.

Automatic switch-off function after 10 minutes. It has an energyfriendly ARM process chip, for fast calculation of measurement results.

- For use on solid materials
- Large display
- Built-in rechargeable battery
- Automatic switch-off function

Product details	
Item no.	15215015
EAN	5708004053606
Customs tariff	9025808090
Sales Quantity	1

## **Product specifications**

Barcode	5708004053606
Working temperature	-20°C - 40°C
Auto power off	Yes
Battery	3,7V lithium Ion
Data output	Nej
Dimensions	110 x 81 x 32 mm
Measuring range	Ra, Rq: 0,05-10,0 μm. Rz, Rt: 0,1- 50,0 μm
Measuring range Resolution	
	50,0 µm
Resolution	50,0 μm 0,001 μm
Resolution Parameters	50,0 μm 0,001 μm Ra, Rz, Rq, Rt

