



Surface Roughness Tester 4 standards, Ra, Rz, Rq, Rt

15215015

This simple roughness tester has been developed for use in the workplace, for quick and easy control of milled, turned, sanded surfaces, on steel and other similar solid materials.

The roughness tester has a large display 45 x 19 mm (front) and 25 x 6 mm (top). It has a built-in rechargeable Lithium-ion battery (without memory effect), with a working time of approx. 20 hours.

Automatic switch-off function after 10 minutes. It has an energy-friendly ARM process chip, for fast calculation of measurement results.

- For use on solid materials
- Large display
- Built-in rechargeable battery
- Automatic switch-off function

Product details

Item no.	15215015
EAN	5708004053606
Customs tariff	9024809000
Sales Quantity	1

Product specifications

Barcode	5708004053606
Working temperature	-20°C - 40°C
Auto power off	Yes
Battery	3,7V lithium Ion
Data output	Nej
Dimensions	110 x 81 x 32 mm
Measuring range	Ra, Rq: 0,05-10,0 μm. Rz, Rt: 0,1-50,0 μm
Resolution	0,001 μm
Parameters	Ra, Rz, Rq, Rt
Test length	0,25/0,80/2,50
Gross weight	1.520 kg
Net weight	0.750 kg