



SYLVAC Digital Indicator S_DIAL WORK BASIC 25 x 0,01 mm IP51 (805.1401)

SYL8051401

Can be used with Sylcom software. Data output: USB / RS232.
Functions: Min/Max/Delta, Preset (max. 99.999), conversion factor, reset.

Battery: 1xCR2032 included.

- Data output Proximity til USB/RS232
- Robust construction
- Water and coolant resistant
- Standard functions (mm/inch, preset, direction of measurement)
- Automatic wake-up and sleeping mode (Absolute System SIS)

Product details

Item no. SYL8051401

EAN

Customs tariff 90178000

Sales Quantity 1

Product specifications

Barcode 7640125026245

Error limit 10 µm

Product type Digital måleur

Brand name SYLVAC

Resolution 0,01 mm

Accuracy 2 µm

SYLVAC item no. 805-1401

Measuring range 0-25 mm

Battery CR2032

IP Class IP51

Data output USB / RS232

Repeatability 2 µm

Diameter Ø59,5 mm

Shank Ø8 h6

Measuring range 0-25 mm

Resolution 0,01 mm

Repeatability 2 µm

IP Class IP51

Data output USB/RS232

Error limit 10 µm

Battery CR2032

Gross weight 0,220 kg