



SYLVAC Digital Test indicator S_DIAL TEST SMART 0,8 x 0,001 mm IP54 key length 12,5 mm (805.4321) BT

SYL8054321

S_Dial TEST Smart with completely new internal mechanics that ensures direct transmission and thus eliminates hysteresis errors. With IP54 enclosure class, the instrument is perfect for use in harsher workshop environments.

Available in three different models with a key length of 12.5 mm or 36.5 mm and a model with replaceable key points (12.5 mm + 36.5 mm can be used on one and the same housing).

Battery: 1xCR2032 included.

- Data output: Bluetooth and proximity to USB/RS232
- Digital and analog display
- Water and coolant resistant IP54
- Automatic switch OFF
- Stem Ø 8 mm and dovetail back
- Rotating display over 360°
- Calibration certificate included

Product details

Item no. SYL8054321

EAN

Customs tariff 90178000

Sales Quantity 1

Product specifications

Barcode 7640125688931

Battery CR2032

Scale 0,001 mm

Diameter Ø45,3 mm

Measuring range 0,8 mm

Resolution 0.001 mm

Accuracy 3 µm

Repeatability 1 µm

IP Class IP54

Data output Bluetooth/USB/RS232

Probe length 12,5 mm

Kalibreringscertifikat ✓

Gross weight 0.130 kg

Net weight 0.130 kg