



## Ultrasonic Thickness Gauge Through-Coating with measurement modes T-E,E-E

**15082650**

An advanced ultrasonic thickness gauge for measuring wall thicknesses (T-E) as well as Through-Coating measurements (E-E) such as paint/primer layers.

The supplied probe is automatically recognized by the device during start-up and also performs an automatic zero calibration - the last sound velocity setting is used automatically making the gauge ready within seconds to perform measurements.

Installed with 9 material settings - an additional 4 individual materials/velocities can be stored. Total memory of 5200 measurements by 26 file sets. USB Data output.

### Product details

|                |               |
|----------------|---------------|
| Item no.       | 15082650      |
| EAN            | 5708004032625 |
| Customs tariff | 90173000      |
| Sales Quantity | 1             |

### Product specifications

|                 |  |
|-----------------|--|
| Barcode         | 5708004032625  |
| Resolution      | 0,01 mm  |
| Battery         | 2 x AAA  |
| Data output     | USB  |
| Display type    | TFT display 320x240  |
| Measuring range | T-E: 0,65-400 mm / E-E: 3-25 mm  |
| Accuracy        | ± 0,04 mm < 9,99 mm /<br>± 0,1% + 0,04 mm = 10-99,9 /<br>± 0,3% > 100 mm |
| Product size    | 133x75x29 mm   |
| Power supply    | 2 x AAA  |
| Gross weight    | 1.300 kg   |
| Net weight      | 1.300 kg   |