



X300 Coating thickness gauge 0-3000μm external probe Bluetooth to App Xthick

15079530

X300 Coating Thickness Gauge 0-3000μm with External Probe, Bluetooth to XThick App

Flexible coating thickness gauge with an external ruby probe combining Fe + NFe, making it suitable for measurements in confined spaces. It is used for measuring, for example, paint and coating thicknesses on both magnetic and non-magnetic metals. For instance, it measures galvanizing, paint, zinc, plastic coating, aluminum, copper, and more.

Features:

- Measuring paint thickness on cars, ship repairs, galvanizing, and measuring felt thickness, etc.
- External combined probe (Fe) 0-3000μm for iron, stainless steel + (NFe) 0-3000μm for aluminum and copper
- The instrument has automatic substrate recognition.
- Accuracy: $\pm 2\% + 1\mu\text{m}$ under 2000μm / $\pm 3\% + 2\mu\text{m}$ up to 3000μm.
- Measurement units: μm, mm, inches.
- Measures galvanizing, paint, zinc, aluminum, copper, plastic coatings.
- Supports zero calibration.
- Suitable for measurements in confined spaces.
- Automatic rotating screen

Product details

Item no. 15079530

EAN

Customs tariff 9017300000

Sales Quantity 1

Product specifications

Barcode 5708004108917

Resolution 0.1μm (0~99.9μm); 1μm ($\geq 100\mu\text{m}$)

Accuracy $\pm(2\% + 1\mu\text{m})$

Measuring range 0-3000 μm

Gross weight 0.570 kg

Net weight 0.470 kg